

Model	Nominal capacities CO ₂ DX		Draw-through AC fans 230-400/50/3							Connections		Stock model
	DT1 +2/-8 °C kW	SC2 kW	fan power nr.	air throw W	air throw m	sound pressure dB(A)	air flow m ³ /h	coil surface m ²	Int. volume dm ³	OD in mm	OD out mm	
Fin spacing 4 mm. fan speed H												
CCXH401 A 4	6.4	4.8	1	280	16.6	53	3777	17.4	2.1	12	10	-
CCXH401 B 4	8.3	6.2	1	280	15.5	53	3528	26.0	3.2	12	10	-
CCXH401 C 4	9.1	6.8	1	280	14.5	53	3307	34.7	4.3	12	12	-
CCXH402 A 4	12.7	9.5	2	560	23.6	56	7509	33.9	3.8	12	12	-
CCXH402 B 4	16.4	12.2	2	560	21.9	56	6997	50.8	5.7	16	14	-
CCXH402 C 4	18.8	14.1	2	560	20.5	56	6546	67.8	7.6	16	14	-
CCXH403 A 4	18.9	14.1	3	840	28.9	58	11240	50.4	5.5	16	16	-
CCXH403 B 4	24.5	18.3	3	840	26.9	58	10470	75.6	8.2	16	16	-
CCXH403 C 4	26.9	20.3	3	840	25.2	58	9783	100.8	10.9	16	16	-
CCXH404 A 4	25.6	19.1	4	1120	33.4	59	14970	67.0	7.1	16	16	-
CCXH404 B 4	30.9	23.3	4	1120	31.1	59	13930	100.4	10.7	16	16	-
CCXH404 C 4	35.8	27.0	4	1120	29.1	59	13020	133.9	14.3	22	16	-
CCXH501 A 4	12.4	9.3	1	720	23.9	55	7447	32.3	3.8	12	12	-
CCXH501 B 4	16.3	12.2	1	720	22.8	55	7097	48.5	5.7	16	12	-
CCXH501 C 4	19.0	14.2	1	720	21.8	55	6782	64.7	7.6	16	12	-
CCXH502 A 4	23.1	17.5	2	1440	34.0	58	14850	63.6	6.9	16	16	-
CCXH502 B 4	29.7	22.5	2	1440	32.4	58	14140	95.3	10.4	16	16	-
CCXH502 C 4	36.2	27.3	2	1440	30.9	58	13490	127.1	13.8	22	16	-
CCXH503 A 4	36.9	27.5	3	2160	41.7	60	22250	94.8	10.1	22	16	-
CCXH503 B 4	44.5	33.7	3	2160	39.7	60	21170	142.2	15.1	22	16	-
CCXH503 C 4	52.7	39.9	3	2160	37.9	60	20200	189.6	20.1	22	18	-
CCXH504 A 4	46.2	34.8	4	2880	48.2	61	29660	126.0	13.2	22	18	-
CCXH504 B 4	61.3	46.2	4	2880	45.9	61	28210	189.0	19.8	22	22	-
Fin spacing 4 mm. fan speed L												
CCXL401 A 4	4.9	3.6	1	120	10.1	43	2295	17.4	2.1	12	10	-
CCXL401 B 4	6.1	4.5	1	120	9.4	43	2135	26.0	3.2	12	10	-
CCXL401 C 4	6.5	4.9	1	120	8.7	43	1995	34.7	4.3	12	12	-
CCXL402 A 4	9.6	7.2	2	240	14.3	46	4562	33.9	3.8	12	12	-
CCXL402 B 4	12.0	8.9	2	240	13.3	46	4232	50.8	5.7	16	14	-
CCXL402 C 4	13.3	9.9	2	240	12.4	46	3946	67.8	7.6	16	14	-
CCXL403 A 4	14.4	10.8	3	360	17.6	48	6828	50.4	5.5	16	16	-
CCXL403 B 4	17.9	13.4	3	360	16.3	48	6328	75.6	8.2	16	16	-
CCXL403 C 4	19.3	14.5	3	360	15.2	48	5897	100.8	10.9	16	16	-
CCXL404 A 4	19.4	14.4	4	480	20.3	49	9094	67.0	7.1	16	16	-
CCXL404 B 4	23.1	17.3	4	480	18.8	49	8425	100.4	10.7	16	16	-
CCXL404 C 4	25.7	19.3	4	480	17.5	49	7848	133.9	14.3	22	16	-
CCXL501 A 4	9.9	7.4	1	290	15.7	45	4880	32.3	3.8	12	12	-
CCXL501 B 4	12.6	9.4	1	290	15.0	45	4656	48.5	5.7	16	12	-
CCXL501 C 4	14.3	10.7	1	290	14.3	45	4447	64.7	7.6	16	12	-
CCXL502 A 4	18.8	14.1	2	580	22.3	48	9732	63.6	6.9	16	16	-
CCXL502 B 4	23.6	17.8	2	580	21.2	48	9274	95.3	10.4	16	16	-
CCXL502 C 4	27.7	20.8	2	580	20.3	48	8846	127.1	13.8	22	16	-
CCXL503 A 4	29.3	21.9	3	870	27.3	50	14580	94.8	10.1	22	16	-
CCXL503 B 4	35.4	26.7	3	870	26.1	50	13890	142.2	15.1	22	16	-
CCXL503 C 4	40.7	30.6	3	870	24.8	50	13240	189.6	20.1	22	18	-
CCXL504 A 4	37.5	28.2	4	1160	31.6	51	19430	126.0	13.2	22	18	-
CCXL504 B 4	48.2	36.2	4	1160	30.1	51	18510	189.0	19.8	22	22	-